

General Information

Dimensions	18 x 21 x 18 inches
Weight	60 - 65 lbs
Motor	DC, 50/60 Hz
Materials	Stainless Steel, Lexan, Delrin, Nylon, Anodized Aluminum
Warranty	6 months parts and labor. Motor warranty by manufacturer.
Lubrication	Spray a light coating of mineral oil on all linking heads immediately after washdown. Lubricate the 3 grease fittings weekly.
Installation	Installation, initial startup and adjustments performed by qualified Nitta personnel. Nitta provides training for operators and maintenance staff.

The Z-Linker Models

	Model II	Model III
Linking Heads	8 Linking Heads	12 Linking Heads
Links per Min	240 - 360	400 - 600
Application	Major manufacturers	High productivity for major manufacturers
Features		Variable speed control provides even flow

Cam Combinations

The Z-Linker can accommodate casings sizes from 17 – 32 mm, without any machine adjustments.

Stuffing Horns are also available from O.D. 8mm to 19mm. All are compatible with current stuffing equipment.

Other sizes require customized configurations. Link size capabilities are not limited to those listed on this chart. Our Nitta Casings equipment experts will assist you by recommending the best combinations to meet your process needs.

Nitta Casings provides full support of the Z-Linker machinery with complete training and service.

Product Code	Cam Letter	Guard Size	Link Length	
00x07	A	Sm	3 - 3/4	M O D E L I & II M O D E L III
00x08	B	Sm	3 - 7/8	
00x09	C	Md	4 - 3/16	
00x10	D	Lg	4 - 1/2	
00x11	E	Sm	3 - 5/8	
00x12	F	Lg	2 - 1/2 or 5	
00x13	G	Sm	3 - 1/2	
00x14	H	Sm	3 - 3/4 (6hd)	
00x15	I	Sm	3 - 1/2 (6hd)*	
00x16	J	Sm	3 - 7/8 (6hd)	
00x17	K	Sm	4 - 1/2 (6hd)	
00x18	L	Lg	6 (6hd)	
01x70	M	Sm	3 - 5/8	
01x72	N	Sm	3 - 1/2	
02x22	OM2	Md	4 - 1/8	
12x50		Lg	3.5	
12x51		Lg	3.625	
12x52		Lg	3.750	
12x53		Lg	3.875	
12x54		Lg	4	
12x56		Lg	4.25	
12x59		Lg	3.437	